

# 3625 HT VC

Compactor with vibration crusher drum


Compactors Series 3000 / Series H177




## HIGHLIGHTS 3000

- > Flexible application thanks to change holder system
- > For breaking up or crushing hard materials
- > Crushes and compacts
- > With high point load thanks to the latest chiselling technology
- > Barrel bands enable safe transportation and loading
- > Heavy-duty equipment

Machine dimensions		
Total length (L)	mm	6591
Width (B)	mm	2540
Total height (H)	mm	3065
Drum width (X)	mm	2220
Height loading, min. (Hl)	mm	2360



**TIER 3**  
EU Stage IIIA / EPA Tier 3

TECHNICAL DATA		Unit	3625 HT VC
	<b>Weights</b>		
	Operating weight with cab	kg	25420
	Operating weight, max.	kg	25940
	Axle load, front/rear	kg	17075/8345
	<b>Machine dimensions</b>		
	Total length	mm	6591
	Total height with cab	mm	3065
	Height loading, min.	mm	2360
	Wheel base	mm	3186
	Ground clearance, centre	mm	420
	Total width with cab	mm	2540
	Turning radius, inside	mm	4590
	Angle of driving slope, front/rear	°	45/27
	<b>Drum dimensions</b>		
	Drum width, front	mm	2220
	Drum diameter, front	mm	1710
	Drum type, front		VC
	Drum thickness, front	mm	35
	<b>Wheel dimensions</b>		
	Size of tyres, rear		EM 23.5-R25 XTLA
	<b>Diesel engine</b>		
	Manufacturer		DEUTZ
	Version		TCD 2012 L06 2V
	Number of cylinders		6
	Power rat. ISO 14396, kW/PS/rpm		155,0/210,8/2300
	Power rating SAE J1349, kW/HP/rpm		155,0/207,7/2300
	Emissions standard EU/USA		EU Stage IIIA / EPA Tier 3
	<b>Drive</b>		
	Speed, infinitely variable	km/h	0 - 8,0
	Regulation, infinitely variable		Hammtronic
	Climbing ability, vibration on/off	%	61/66
	<b>Vibration</b>		
	Vibration frequency, front	Hz	27
	Amplitude, front	mm	2,09
	Centrifugal force, front	kN	351
	<b>Steering</b>		
	Oscillation angle +/-	°	10
	Steering, type		Articulated steering
	<b>Tank capacity/Fill capacity</b>		
	Fuel tank, capacity	L	290
	<b>Sound level</b>		
	Acoustic power LW(A), sticker		110
	Acoustic power LW(A), measured		105

#### EQUIPMENT

2 armrests, 3-point articulation, Adjustable scraper, Dashboard with displays, indicator lights and switches, Automatic traction control and anti-slip control, Battery isolation switch, Control console with steering column adjustment, Operator's platform with entry from both sides, Speed preselect, Hydrostatic steering, Vibration-isolated operator's platform, Stepless hydrostatic all-wheel drive, Handrails on the operator's platform, Sound insulation

#### OPTIONAL EQUIPMENT

Working lights, Back-up alarm (reversing), HAMM Compaction Meter, Radio, ROPS, rigid, Rotating beacon, Hydraulic hose protection on front frame, Protective roof, Version with additional fuel prefilter, Auxiliary heater, ROPS cabin, ROPS cabin with heating, ROPS cabin with heating and air conditioning, Rear area camera, HCQ Navigator, Telematics interface, Protective grille for lighting package

**HAMM AG**  
Hammstraße 1  
D-95643 Tirschenreuth  
Tel. +49 9631 80-0  
Fax +49 9631 80-111  
www.hamm.eu



**HAMM**