


TECHNICAL INFORMATION | TRACK-MOUNTED JAW CRUSHERS

# MOBICAT MC 125 Z





## TECHNICAL HIGHLIGHTS

- ▣ Frequency-controlled vibrating feeder
- ▣ Diesel-electric drive concept
- ▣ Option for external power supply (optional)
- ▣ Independent vibrating double-deck prescreen

## TECHNICAL INFORMATION MC 125 Z

### Feeding unit

Feed capacity up to approx. (t/h) <sup>1)</sup>	600
Feed size max. (mm)	1,125 x 700
Feed height (with extension) (mm)	5,800 (6,500 / 7,200)
Width x Length (with extension) (mm)	3,250 x 4,500
Hopper volume (with extension) (m <sup>3</sup> )	10 (15/30)

### Vibrating feeder

Width x Length (mm)	1,200 x 3,500
---------------------	---------------

### Prescreening

Type	double-deck heavy-piece screen
Width x Length (mm)	1,250 x 3,000

### Side discharge conveyor (optional)

Width x Length (extended) (mm)	1,000 x 8,000
Discharge height approx. (extended) (mm)	4,000

### Crusher

Single toggle jaw crusher type	STR 1,250 x 1,000
Crusher inlet width x depth (mm)	1,250 x 1,000
Crusher weight approx. (kg)	49,000
Crusher drive type approx. (kW)	electric, 200
Adjustment range of gap width (mm) <sup>2)</sup>	80 - 250
Crusher gap adjustment	hydraulically supported

### Crushing capacity<sup>3)</sup>

with CSS 100 mm: approx. from - to (t/h)	175 - 230
with CSS 130 mm: approx. from - to (t/h)	230 - 295
with CSS 160 mm: approx. from - to (t/h)	285 - 360
with CSS 200 mm: approx. from - to (t/h)	355 - 445
with CSS 250 mm: approx. from - to (t/h)	450 - 550

### Vibrating extractor

Width x Length (mm)	1,200 x 2,600
---------------------	---------------

### Crusher discharge conveyor

Width x Length (mm)	1,200 x 9,900
Width x Length without vibrating extractor (option) (mm)	1,200 x 12,000
Discharge height approx. (mm)	4,200
Discharge height without vibrating extractor (option) (mm)	4,000

### Power supply unit

Drive concept	diesel-electric drive
Scania (LRC) (kW)	364 (1,500 rpm)
Scania (Tier 3/Stage IIIA) (kW)	364 (1,500 rpm)
Generator (kVA)	550

### Weight

Total weight without options approx. (kg)	130,000
---	---------

<sup>1)</sup> dependent on the type and composition of the feed material, the feed size, the prescreening, as well as the desired final grain size

<sup>2)</sup> gap width range can be changed by using special crusher jaws and/or pressure plates

<sup>3)</sup> for hard stone, CSS = Close Side Setting

**Standard features:** Feed hopper / Frequency-controlled vibrating feeder / Ultrasonic probe at crusher inlet / Radio remote control / PLC control with LCD display / Control cabinet, with double dust encapsulation, lockable, suspended and with over pressure system / Lighting

**Options:** Hopper extension / Side discharge conveyor / Electromagnetic separator, permanent magnet, magnet preparation / Long crusher discharge conveyor instead of vibrating extractor / Preparation for installation of belt scale / Belt covers (aluminium, tarpaulin) / Remote maintenance using GSM modem / Extension for crusher discharge conveyor (hydraulically foldable) / External power supply / Rock chisel / Socket 110 V / Spray system for dust reduction