




TECHNICAL SPECIFICATIONS | TRACK-MOUNTED SCREENING PLANT

MOBISCREEN MS 19 Z





TECHNICAL HIGHLIGHTS

- ▣ Double-deck screening unit
- ▣ Diesel-hydraulic drive
- ▣ Classifier screen for three final products
- ▣ Max. feed size: 150 mm

TECHNICAL SPECIFICATIONS MS 19 Z

Feeding unit

Feed capacity up to approx. (t/h)	500
Feed size max. (mm)	150
Feed height (mm)	3,635
Hopper capacity (m ³)	8

Belt conveyor feeder

Width x length (mm)	1,200 x 3,500
Type (optional)	variable speed

Feeding belt conveyor screen

Width x length (mm)	1,050 x 11,800
---------------------	----------------

Screening unit

Type	double-deck vibration screen
Top deck width x length (mm)	1,520 x 6,100
Bottom deck width x length (mm)	1,520 x 5,490

Bottom deck underflow discharge conveyor (fine fractions)

Width x length (mm)	1,200 x 8,000
Discharge height approx. (mm)	4,600

Bottom deck overflow

discharge conveyor (medium fractions)

Width x length (mm)	800 x 10,300
Discharge height approx. (mm)	5,100

Top deck overflow

discharge conveyor (oversize fractions)

Width x length (mm)	800 x 10,300
Discharge height approx. (mm)	5,100

Drive

Drive concept	Diesel-hydraulic drive
Powerpack CAT (Tier 3, 4i,4f) (kW)	95

Transport

Transport height approx. (mm)	3,400
Transport length approx. (mm)	17,820
Transport width approx. (mm)	3,000
Transport weight approx. (kg)	36,000