

R135 GEN:2

COMPACT LOADERS



Key Features

- ✓ Loft Effort Control Choices
- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Self-Leveling Hydraulic Lift Action
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar or Hand/Foot Control System
- ✓ Audible Back-Up Alarm
- ✓ Standard High Back Cushion Seat

Key Specifications

- ✓ Operating Capacity (50%) - 612 kg (1,350 lbs.)
- ✓ Overall height to top of ROPS - 1930 mm (76")
- ✓ Gross Power - 34.3 kW (46.6 hp) @ 2800 rpm
- ✓ Yanmar / 4TNV88-BKMSR2 / Stage 3A
- ✓ 146.2 Nm (108 ft.-lbs.) @ 1820 rpm max torque
- ✓ 2784 mm (110") height to hinge pin
- ✓ 1364 mm (53.7") machine width - less bucket
- ✓ 2327 kg (5,130 lbs.) operating weight

SPECIFICATIONS

METRIC		
Capacities	Rated Operating Capacity	612.34 kg
	Rated Operating Capacity with Optional Counterweight	680 kg
	Unladen weight	2383.62 kg
Weight and dimensions	Wheelbase	950 mm
	Overall Operating Height - Fully Raised	3670.30 mm
	Height to Hinge Pin - Fully Raised	2790 mm
	Dump angle at full height	40 °
	Dump height	2120 mm
	Overall length with bucket	3073.40 mm
	Dump reach - Full height	591 mm
	Rollback at ground	28 °
	Seat to ground height	871.22 mm
	Overall width less bucket	1364 mm
	Bucket Width	1372 mm
	Ground clearance	201 mm
	Overall length - Less Bucket	2359.66 mm
	Clearance Radius - Front with Bucket	1842 mm
	Rear departure angle	25 °
Performances	Travel speed (unladen)	12.90 km/h
Wheels	Standard tires	10.00 x 16.5 HD
Engine	Engine brand	Yanmar
	Engine model	4TNV88C
	Engine norm	Stage V, Tier 4 final
	Gross Power	34.30 kW
	Max. torque / Engine rotation	146.20 Nm / 1820 rpm
	Power source	Diesel
	Battery voltage	12 V
	Starter	2.30 kW
Hydraulics	Standard flow - Auxiliary hydraulics	63.60 l/min
Tank capacities	Fuel tank	59.40 l
	Hydraulic tank capacity	34.80 l
	Displacement	2.19 l
Noise and vibration	Noise to environment (LwA)	101 dB
	Whole-Body Vibration (ISO 2631-1)	0.81 m/s²
	Vibration on hands/arms	< 1.77 m/s²



Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT