

V210

SKID LOADER



KEY FEATURES

- **NEW** Color Display with Keyless Start + Security Code
- **NOW STANDARD** Pilot Joystick Controls
- **NEW** Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- Auxiliary Hydraulics with Drain Case
- **NEW** LED Work, LED Rear Lights + Egress Lighting
- Vertical Lift Arm for More Reach at Dump Height
- **NOW STANDARD** Hydraglide™ Ride Control
- **NEW** Greasable Pins for Reduced TCO
- Flip-Up Cooler with Hydraulic Fan
- **NOW STANDARD** Backup Alarm



V210 SKID LOADER



SPECIFICATIONS

	METRIC	IMPERIAL	
WEIGHT & DIMENSIONS	Operating Weight	3393 kg	7480 lbs
	Overall Operating Height - Fully Raised	4013 mm	158"
	Height to Hinge Pin - Fully Raised	3061 mm	120.5"
	Overall Height to Top of ROPS	2032 mm	80"
	Dump Angle at Full Height	42°	
	Dump Height - Fully Raised	2286 mm	90"
	Rollback Angle Fully Raised	92°	
	Overall Length with Bucket	3543 mm	139.5"
	Dump Reach at Full Height	851 mm	33.5"
	Rollback Angle at Ground	29°	
	Seat to Ground Height	952.5 mm	37.5"
	Crawler Base	1092 mm	43"
	Overall Width - Less Bucket	1623 mm	63.9"
	Ground Clearance to Chassis	178 mm	7"
	Overall Length without Bucket	2743 mm	108"
	Specified Height	2184 mm	86"
	Reach at Specified Height	902 mm	35.5"
	Departure Angle	25°	
	Clearance Radius - Front with Bucket	2146 mm	84.5"
	Clearance Radius - Front without Bucket	1308 mm	51.5"
Clearance Radius - Rear	1664 mm	65.5"	
Bucket Width	1676 mm	66"	
Standard Tire Width	10 x 16.5		
CAPACITIES	Operating Capacity at 50% Tipping Load	952 kg	2100 lbs
	Operating Capacity at 50% Tipping Load with Optional Side Weights	1021 kg	2250 lbs
ENGINE	Make / Model	Yanmar / 4TNV98C-NGL	
	Type	Stage 5	
	Gross Power	51.7 kW	69.3 HP
	Net Power	51 kW	68.4 hp
	Maximum Torque @ 1625 rpm	241 Nm	178 ft/lbs
	Battery	3.0 kW	12 V
PERFORMANCE	Travel Speed	12.1 km/hr	7.5 mph
	Travel Speed with 2-Speed Option	18.7 km/hr	11.6 mph

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.

STANDARD FEATURES

- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- NEW Back-Up Alarm
- NEW Battery Disconnect
- Brake Control (Auto/Manual)
- NEW Color Display with Keyless Start + Security Code
- NEW Egress Lighting with Time Delay
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- Hand Throttle
- Foot Throttle / NEW Deceleration Pedal
- High-Back Adjustable Seats
- Horn
- Hydraloc™ Safety System
- NEW Hydraglide™ Ride Control
- NEW Hydraulic Variable Speed Fan
- Hydrostatic Drive - Servo
- Integral Access Plate (removable)
- NEW LED Tail + Work Lights
- NEW Lift Arm Shape for Improved Visibility
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Operated Joystick Controls
- Flip-up Cooler
- 12-Volt + USB Charging Ports
- One Speed Drive
- Slope Roof
- Manual Attach
- 4-Point Lift
- Sound Reduction Package

OPTIONAL FEATURES

- 14-Pin Attachment Control
- Air Conditioning + Heating with Cab Enclosure
- Bluetooth Hands-Free Radio
- Cast Rear Bumper
- NEW Creep Mode Adjustable
- Door Options: Swing-Out, Fold-Up or Impact
- Engine Pre-Cleaner
- High-Flow Auxiliary Hydraulics
- Hydraulic Power-A-Tach® Attachment Mounting System
- NEW Impact Side Windows
- NEW LED Road Light Package
- NEW LED Side Lights
- FOPS Level II with Light Guard
- Rear Window Wiper
- Rearview Camera
- Rearview Mirror
- NEW Reversible Cooling Fan
- Selectable Self-Leveling Hydraulic Lift Action
- Side Counterweights
- Suspension Seat - Air Ride or Mechanical
- NEW Cloth, Heated Seat with Air Suspension + Extended Backrest
- Two-Speed Drive
- 4-Way Flashers
- Sliding Side Windows



GEHL COMPACT EQUIPMENT

West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517