

NPK[®]



 **MOVITER**

MULTIPROCESSADORES



CATÁLOGO DE GAMA

Multiprocessador



Demolição primária



Tipo S

Demolição secundária



Tipo G

Para corte de metal






Tipo K

Modelo	M-20S	M-20G	M-20K	M-28S	M-28G	M-28K	M-38S	M-38G	M-38K
Peso da escavadora (t)	17 - 24	17 - 24	17 - 24	28 - 40	28 - 40	28 - 40	35 - 45	35 - 45	35 - 45
Peso (kg)	2000	2100	2100	2970	3150	3130	3850	4150	4250
Abertura máx. das mandíbulas (mm)	940	770	540	1067	910	638	1230	1140	735
Pressão (MPa)	25	25	25	25	25	25	25	25	25
Fluxo de óleo (l/min)	100 - 250	100 - 250	100 - 250	150 - 350	150 - 350	150 - 350	175 - 400	175 - 400	175 - 400
Pressão de rotação (MPa)	14	14	14	14	14	14	14	14	14
Fluxo de óleo de rotação (l/min)	10 - 15	10 - 15	10 - 15	10 - 30	10 - 30	10 - 30	10 - 30	10 - 30	10 - 30
Força máx. (A) (kN)	690	740	800	1030	1120	1190	1300	1360	1510
Força máx. (B) (kN)	1070	1250	1480	1400	1500	1700	2000	2000	2680
Força máx. (C) (kN)	3250	-	-	4500	-	-	5900	-	-



Tecnologia “power booster“



Model	M-20S	M-20G	M-20K	M-28S	M-28G	M-28K	M-38S	M-38G	M-38K
Abertura (s)	1,1	1,1	1,1	1,5	1,5	1,5	2,0	2,0	2,0
Fecho (s)	2,2	2,2	2,2	2,7	2,7	2,7	3,6	3,6	3,6
Ciclo completo (s)	3,3	3,3	3,3	4,2	4,2	4,2	5,6	5,6	5,6
Número de ciclos (n/min)	18	18	18	14	14	14	11	11	11
Fluxo de óleo (l/min)	250	250	250	350	350	350	400	400	400
L1 (mm)	2276	2268	2376	2631	2652	2716	3200	3250	3325
L2 (mm)	401	393	501	542	505	627	781	709	654
P1 (mm)	940	770	540	1067	910	638	1230	1140	735
P2 (mm)	1245	1181	1052	1517	1480	1273	1670	1665	1495

MARTELOS			PULVERIZADORES
BATE ESTACAS			ESMAGADORES
TESOURAS DE SUCATAS			TESOURAS
SOLUÇÕES X-Y-Z			PINÇAS DE DEMOLIÇÃO
COMPACTADORES			MULTI PROCESSADORES



Parque Movicortes, 2404-006 Azoia, Leiria
T. (+351) 244 850 240 / moviter@movicortes.pt / www.moviter.pt
Lisboa, Maia, Évora, Funchal, Luanda, Maputo, Casablanca, Conacri